

twilight

INSTRUMENTOS DE MEDICIÓN INDUSTRIAL

Estándar de Viscosidad

N35

CA-N35

www.twilight.mx

 / [twightsadecv](#)

 / [twightsadecv](#)

 / [twightsadecv](#)

SPECIFICATIONS:

Based on NIST value of 1.0016 centipoise for water at 20C; conforms to ASTM Standards D 445, D 88 and D 2161; traceable to NIST

TABLE 1: Kinematic Viscosity, cSt / Centipoise

Thomas No.	Visc. Std.	20°C 68°F	25°C 77°F	37.78°C 100°F	40°C 104°F
9727C37	N35	87 / 76	66 / 57	35 / 30	32 / 27

TABLE 1: Kinematic Viscosity, cSt / Centipoise (continued)

Thomas No.	Visc. Std.	50°C 122°F	60°C 140°F	98.89°C 210°F	100°C 212°F
9727C37	N35	21 / 18	- / -	5.4 / 4.4	5.3 / 4.3

TABLE 2: Approximate Saybolt Viscosity

Thomas No.	Visc. Std.	100°F	Saybolt Universal Seconds 210°F	Saybolt Furol Seconds, 122°F
9727C37	N35	170	-	-



INSTRUMENTOS DE MEDICIÓN INDUSTRIAL

 LLÁMANOS

+52(81) 8115-1400 / +52 (81) 8173-4300

LADA Sin Costo:
01 800 087 43 75

E-mail:
ventas@twilight.mx

www.twilight.mx

