

Analizador portátil de fluorescencia de rayos X ElvaX ProSpector 2 LE EL-PROSPECTOR2

www.twilight.mx







INSTANT XRF ANALYSIS RESULTS EVERYWHERE AND ANYTIME ProSpector 2



ProSpector 2 is our time-tested handheld XRF analyzer.

Due to the advanced electronics and state-of-the-art mathematical algorithms, ProSpector 2 provides ultimate quality of measurement within a couple of seconds. It is an intuitive and user-friendly instrument for highly accurate elemental analysis in a variety of applications

ACCURACY

With powerful hardware and unique software algorithms, the ProSpector 2 offers the highest precision and accuracy of elemental analysis for a wide range of materials

SPEED

Dynamically Adaptive Shaping (DAS) DPP developed by Elvatech combined with the Fast SDD detector makes the ProSpector 2 the fastest handheld XRF analyzer on the market

STABILITY

Thanks to the digiX-40 digital X-Ray source, automatic temperature and barometric corrections, and digital calibration adjustment, ProSpector 2 offers long-life reproducibility of the analysis without the need to re-calibrate the system



Shock and water resistant carrying case allows you to take the instrument anywhere you need it.

An adaptor for weld joints analysis focuses X-Ray spot on a weld joint excluding surrounding material



Use a laboratory stand to prevent X-Ray scattering when analyzing small objects or light matrix samples.



- High speed of operation @ above 500 000 CPS count rate
- Ambient temperature and pressure corrections for highest stability
- 🞯 Over 10 hours operation from the battery
- Ø Detector protection
- 🧭 Extensive and editable alloy grade library
- Ore Protective film replacement with no tool required
- Sull compatibility with ElvaXTM PC software
- S Radiation safety: IR proximity sensor and low count detection

Instant Analysis Results Print-out with a portable Bluetooth printer provides measurement prints at any time, anywhere



Alloys
Today, 4:34 PM no name
316 Ti (99% match)
Fe: 66.83 ± 0.10% Cr: 16.76 ± 0.07% Ni: 11.64 ± 0.07% Mo: 2.13 ± 0.01% Mn: 1.84 ± 0.07%
Ti: 0.30 ± 0.06%
Cu: 0.30 ± 0.03%



ProSpector 2 is a powerful handheld XRF analyzer, designed by Elvatech. Due to the advanced hardware and unique software algorithms, ProSpector 2 provides ultimate speed and accuracy of the elemental analysis. ProSpector 2 combines powerful analytical software toolkit with an easy-to-use interface, allowing even novice operators to perform any necessary measurements in seconds.

Digital X-Ray Source digiX-40

Anode: Rh, W Voltage: 40 kV Current: 200 uAmp Power: 4 W 5 positions filter changer

X-Ray Detector

Type: Fast SDD (optional PIN) Area: 25 mm2 Energy resolution: <140 eV @ 5.9 keV Count rate: 500,000 cps

Electronics

DPP: proprietary DAS (Dynamically Adaptive Shaping) type, 80 MHz sampling rate MCA: 4096 channels Display: 4.3' Connectivity: USB, Bluetooth High resolution video camera (option)

General

Dimensions: 242 x 230 x 78 mm Weight: 1.4 kg

Software

Operating system: Windows EC7 Analysis algorithms: Fundamental parameters (FPA), Empirical (regression) calibrations

Riterium

Summer Autor



LLÁMANOS+52(81) 8115-1400 / + 52(81) 8676 2446

LADA Sin Costo: 01 800 087 43 75

E-mail: ventas@twilight.mx

www.twilight.mx





