

Termohigrómetro De Panel HT-HE230A

www.twilight.mx









Features:

- Adopt imported temperature and humidity integrated sensor with high accuracy and stability.
- Measure temperature and humidity with external sensors.
- Key deviation calibration function.
- Large LCD display temperature ,humidity and time simultaneously.
- 100-240VA power supply and wall-mounted design.

LED Display Thermometer Hygrometer							
Model	HE212A	HE218A	HE230A	HE250A	HE218B	HE223H	HE230T
LED size(Inch)	1.2"	1.8"	3.0"	5.0"	1.8"	3.0"	3.0"
Visual range	10M	20M	40M	75M	20M	40M	40M
Temeperature range		-40°C~+85°C					-100°C~ +100°C
Humidity range		0~100%RH					Non
Temeperature accuracy		±0.5°C					±0.5°C
Humidity accuracy		±0.5%RH					±0.5%RH
Sensor type	External 2meters		Externa	PT100 sensor			
N.W.(KG)	0.7	2	.3	5.38		2.3	
Dimension(CM)	17*11.5*3.3	39.5*25.5*5		60.1*38.3*5			36*17.7*8.5
Packing size	24*20*6.6	46*31.5*8.5		66.4*43.3*8.5			46*31.5*10
Standard accessriories	Opration manual						
HE212A visual distance of 10meters HE218A visual distance of 20meters HE230A visual distance of 40meters HE250A visual distance of 75meters						:MP ~ 5 9° C	
						HL	лмі <u>Б 3.Б</u> %

Temperature Humidity Data Logger Model

LED Display Temperature Humidity Data Logger							
Model	HE223C	HE250C	HE218C				
LED size(Inch)	2.3"	5.0"	1.8"				
Visual range	30M	75M	30M				
Temeperature range	-40°C~+85°C						
Humidity range	0~100%RH						
Temeperature accuracy	±0.5°C						
Humidity accuracy	±0.5%RH						
Sensor type	External sensor with 3 meters cable						
N.W.(KG)	2.3	5.38	5.38				
Dimension(CM)	39.5*25.5*5	60.1*38.3*5	60.1*38.3*5				
Packing size	41*31.5*8.5	66.4*43.5*8.5	66.4*43.3*8.5				
Standard accessriories	LogPro Software,operation manual						



ULÁMANOS

+52(81) 8115-1400 / +52 (81) 8173-4300

LADA Sin Costo: **01 800 087 43 75**

E-mail: ventas@twilight.mx



