

twilight

INSTRUMENTOS DE MEDICIÓN INDUSTRIAL

Dinamómetro Uso Rudo Serie ESH/ PSH Rango 100 hasta 300 kgf IM- ESH / IM-PSH

www.twilight.mx

 / [twilightsadecv](https://www.facebook.com/twilightsadecv)

 / [twilightsadecv](https://twitter.com/twilightsadecv)

 / [twilightsadecv](https://www.youtube.com/twilightsadecv)



PSH Ranges

Shaft size: M10, 5/16-18 adapter available

Accuracy: $\pm 0.4\%$ F.S.

Overload Capacity: 135% of rated capacity

[More Ranges](#) ►

<u>Pounds</u>		<u>Kilograms</u>		<u>Newtons</u>	
Model	Capacity (Resolution)	Model	Capacity (Resolution)	Model	Capacity (Resolution)
PSH-200	200 lbf (1 lbf)	PSH-100 kg	100 kgf (0.5 kgf)	PSH-1000 N	1000 N (5 N)

<u>PSH-300</u>	300 lbf (2 lbf)	<u>PSH-200 kg</u>	200 kgf (1 kgf)	<u>PSH-2000</u> <u>N</u>	2000 N (10 N)
<u>PSH-400</u>	400 lbf (2 lbf)	<u>PSH-300 kg</u>	300 kgf (2 kgf)	<u>PSH-3000</u> <u>N</u>	3000 N (20 N)
<u>PSH-500</u>	500 lbf (2.5 lbf)				

PSH Standard Features

- Simple, rugged, virtually maintenance free
- High degree of accuracy
- Capacities up to 500 lbf (push and pull)
- No batteries needed
- Intrinsically safe in hazardous environments
- Rugged design for heavy usage
- Heavy duty metal construction
- Tare ring
- Real time and peak mode
- Full set of accessories and carrying case included

twilight

INSTRUMENTOS DE MEDICIÓN INDUSTRIAL



LLÁMANOS

+52(81) 8115-1400 / +52 (81) 8173-4300

LADA Sin Costo:
01 800 087 43 75

E-mail:
ventas@twilight.mx

www.twilight.mx