

Medidor de actividad de agua modelo inteligente ND-HD6

www.twilight.mx











Specifications:

Model	HD-6
Working environment	Temp: -10°C~50°C
	Humidity: 0~95%RH
Display	Big LCD screen, 128×64 DOTS
Measuring range	Temp: -10~50°C
	aW: 0~1.000aw
Accuracy	Temp: ±0.5°C
	aW: ±0.012aw(@23°C±5°C)
Resolution	Temp:0.1°C
	aW: 0.001 aw
aW repeatability	±0.01aw
Measuring point	1~4 measuring sensor, optional
Measuring time	①timing: 5~40mins
	2 Auto measurement
Average time free from system	18000 hours
fault	

Print function	Measurement finishes Real-time print
Power supply	100~230VAC, 50Hz/60Hz
Power	<10W/each (energy saving)
Dimension	280mm×110mm×300mm
Packing	Portable aluminum boxes for the meter
Data processing	 It can save real-time testing value or final testing result. User can also set time to save data. All data can be transmitted to PC and saved as file/sheet. can set the equipment at PC through software
Calibration	Several point calibrated together or single point calibration



LLÁMANOS +52(81) 8115-1400 / +52 (81) 8173-4300

LADA Sin Costo: 01 800 087 43 75

E-mail: ventas@twilight.mx

www.twilight.mx





