

twilight

INSTRUMENTOS DE MEDICIÓN INDUSTRIAL

Medidor de Oxígeno disuelto

SB-DOG1902

www.twilight.mx



/ [twilightsadecv](#)



/ [twilightsadecv](#)



/ [twilightsadecv](#)

DOG-1902 online Dissolved oxygen meter



Technical Indexes

1. Measuring range: 0.00~1 9.99mg / L Saturation: 0.0~199.9%
2. Resolution: 0. 01 mg/L 0.01%
- 3 Accuracy: $\pm 1.5\%$ F.S
4. Control range: 0.00~1 9.99mg/L 0.0~199.9%
5. Temperature compensation: 0~60°C
6. Output signal: 4-20mA isolated protection output, double current output available, RS485 (optional)
7. Output control mode: On/Off relay output contacts
8. Relay load: Maximum: AC 230V 5A
Maximum: AC | 15V 10A
9. Current output load: Allowable maximum load of 500 Ω .
10. On-ground voltage insulation Degree: minimum load of DC 500V
11. Operating voltage: AC 220V 10%, 50/60Hz
12. Dimensions: 96 × 96 × 115mm
13. Dimension of the hole: 92 × 92mm
14. Weight: 0.8 kg
15. Instrument working conditions:
Ambient temperature: 5 - 35 °C
Air relative humidity: $\leq 80\%$

Except for the earth magnetic field, there is no interference of other strong magnetic field around.

twilight

INSTRUMENTOS DE MEDICIÓN INDUSTRIAL



LLÁMANOS

+52(81) 8115-1400 / +52 (81) 8173-4300

LADA Sin Costo:
01 800 087 43 75

E-mail:
ventas@twilight.mx

www.twilight.mx