

# twilight

INSTRUMENTOS DE MEDICIÓN INDUSTRIAL

Ficha Técnica

## Calibrador de Lazo

[www.twilight.mx](http://www.twilight.mx)

 / [twilightsadecv](https://www.facebook.com/twilightsadecv)

 / [twilightsadecv](https://twitter.com/twilightsadecv)

 / [twilightsadecv](https://www.youtube.com/twilightsadecv)

### Electrical Specifications: (23°C±5°C)

**mA DC Current:** (1KΩ Max. Load, 24V Loop Supply)

Range	Resolution	Accuracy
0 – 4mA	1μA	± 0.025% ± 10μA
4 – 20mA	1μA	± 0.025% ± 5μA
20 – 24mA	1μA	± 0.025% ± 5μA

Beeper warning when output is open and specified output > 1mA

### V DC Voltage

Range	Resolution	Accuracy
0 – 4V	1mV	± 0.05% ± 10mV
4 – 20V	1mV	± 0.05% ± 5 mV
20 – 24V	1mV	± 0.05% ± 5 mV

Beeper warning when output is short and specified output > 100mV

### General Specifications:

Dimension:	88 x 168 x 26 mm (3.46" x 6.61" x 1.03")
Battery Type:	9V Alkaline Battery
Display:	4+ 5 Digits
Power Consumption:	25 mA at 100 Ω load
Operating Temperature:	0C to 50C (32°F to 122°F)
Operating Humidity:	less than 85% relative
Storage Temperature:	-20C to 60C (-4°F to 140°F)
Storage Humidity:	less than 85% relative
Weight:	330g / 11.63 oz
Accessories:	Carrying case x 1; Users Manual x 1; External Battery Pack: 1.5V AA Batteries x 6; 9V Alkaline Battery x 1; Alligator clip x 1

# twilight

INSTRUMENTOS DE MEDICIÓN INDUSTRIAL



**LLÁMANOS**

**+52(81) 8115-1400 / +52 (81) 8173-4300**

LADA Sin Costo:  
**01 800 087 43 75**

E-mail:  
**ventas@twilight.mx**

**www.twilight.mx**



/ **twilightsadecv**



/ **twilightsadecv**



/ **twilightsadecv**