

# twilight

INSTRUMENTOS DE MEDICIÓN INDUSTRIAL

## TES-1160 Termohigrómetro / Barhómetro portátil

### TE-1160

[www.twilight.mx](http://www.twilight.mx)

 / [twilightsadecv](https://www.facebook.com/twilightsadecv)

 / [twilightsadecv](https://twitter.com/twilightsadecv)

 / [twilightsadecv](https://www.youtube.com/twilightsadecv)



# TES-1160/1161 Thermo / Hygro / Barometer

- ❑ Triple LCD displays Barometric pressure, Temperature, and Relative humidity
- ❑ Dew point and Wet bulb temperature reading
- ❑ Absolute humidity, Mixing ratio and Enthalpy reading
- ❑ Water vapor pressure and Water saturation pressure reading
- ❑ Pressure trend and tendency (P3h) reading
- ❑ Heat Index and Humidex reading





# TES-1160/1161 Thermo / Hygro / Barometer

## FEATURES

- Triple LCD displays Barometric pressure, Temperature, and Relative humidity.
- Dew point and Wet bulb temperature reading.
- Absolute humidity, Mixing ratio and Enthalpy reading.
- Water vapor pressure and Water saturation pressure reading.
- Pressure trend and tendency (P3h) reading.
- Heat Index and Humidex reading.
- MAX/MIN with Time Stamp.
- Comparator function.
- Alarm output function.
- Auto power off function.
- Data Hold function.
- Manual data memory and read function.
- Auto data logger function. (1161)
- USB Interface. (1161)

## SPECIFICATIONS

<b>Measurement Range</b>	Humidity : 1% to 99%R.H. Temperature : -20°C to + 60°C (-4°F to +140°F) Atmospheric pressure : 300 to 1200hPa
<b>Resolution</b>	0.1% R.H., 0.1°C, 0.1°F, 0.1hPa
<b>Accuracy</b>	Temperature : ±0.8°C, ±1.5°F Humidity : ±3%RH (at 25°C, 30 to 80% RH). ±5%RH (at 25°C, 0 to 20% RH and 80 to 100% RH). Atmospheric pressure : ±2hPa at 25°C
<b>Sensor type</b>	Humidity : Precision capacitance sensor Temperature : Thermistor sensor Atmospheric pressure : Piezoresistive pressure sensor
<b>Response time</b>	Humidity : 45%R.H. to 95% R.H. ≤ 1min 95%R.H. to 45%R.H. ≤ 3min Temperature : 10°C/2 sec.
<b>Sampling rate</b>	1 sample/second.
<b>Data Memory Capacity</b>	99 sets. (Direct reading from LCD display)
<b>Data Logger Capacity</b>	microSD CARD 4GB (1161)
<b>Operating temperature and humidity</b>	0°C to 60°C, below 95% R.H.
<b>Storage temperature and humidity</b>	-10°C to 60°C, below 70% R.H.
<b>Power supply</b>	006P 9V or IEC6F22, NEDA 1604 battery
<b>Battery life</b>	Approx. 100hours
<b>Dimensions</b>	250×64×24.5mm (9.84"×2.52"×0.96")
<b>Weight</b>	Approx. 200g (7.05oz)
<b>Accessories</b>	Instruction manual, Battery, CD software (1161), Micro-USB cable (1161).
<b>Optional Accessory</b>	AC adaptor DC9V (1161)

# twilight

INSTRUMENTOS DE MEDICIÓN INDUSTRIAL



LLÁMANOS

+52(81) 8115-1400 / +52 (81) 8173-4300

LADA Sin Costo:  
01 800 087 43 75

E-mail:  
[ventas@twilight.mx](mailto:ventas@twilight.mx)

[www.twilight.mx](http://www.twilight.mx)



/ [twightsadecv](https://www.facebook.com/twightsadecv)



/ [twightsadecv](https://twitter.com/twightsadecv)



/ [twightsadecv](https://www.youtube.com/twightsadecv)