

twilight

INSTRUMENTOS DE MEDICIÓN INDUSTRIAL

**Termómetro Infrarrojo Dual (Infrarrojo
-35°C a 500°C y Sonda de Contacto
-150°C a 1350°C)**

TE-1327K

www.twilight.mx

► FEATURES

- °C / °F Selectable.
- Back-light LCD display.
- Laser targeting.
- Maximum / Minimum function.
- Data memory and read function.
- Dual thermometer and Dual display. (1327K)
- Emissivity adjustable. (1327/1327K)
- Audible and visible alarm. (1327/1327K)

► INFRARED THERMOMETER

Display	Backlight LCD display
Measurement Range	-35°C ~ 500°C (-31°F ~ 932°F)
Resolution	0.1°C / 0.2°F
Accuracy	± 2% reading or ± 2°C
Spectral Response	6 ~ 14μm
Field of View	12:1 optics ratio with a 1" min target
Emissivity	0.17 ~ 1.00 , (1326S : fixed 0.95)
Sighting	Laser marker < 1mw

► K-TYPE THERMOMETER (for 1327K)

Measurement Range	-150°C ~ 1350°C (-238°F ~ 1999°F)		
Resolution	0.1°C / 1°C , 0.1°F / 1°F		
Function	Resolution	Range	Accuracy
°C	0.1°C	-150°C ~ 0°C	±(0.2%rdg + 1.0°C)
		0°C ~ 200°C	±(0.1%rdg + 1.0°C)
	1°C	200°C ~ 1350°C	±(0.2%rdg + 2°C)
°F	0.1°F	-238°F ~ 32°F	±(0.2%rdg + 2°F)
		32°F ~ 200°F	±(0.1%rdg + 2°F)
	1°F	200°F ~ 1999°F	±(0.2%rdg + 4°F)

► GENERAL SPECIFICATIONS

Data memory capacity	50 sets (Direct reading from LCD display) (1326S/1327) 99 sets (Direct reading from LCD display) (1327K)
Auto power off	approx. 15 sec
Battery Life	Approx. 100 hours (laser pointer and backlight aren't on use) (Alkaline)
Power Source	One 9V cell (ANSI/NEDA-1604A, IEC-6LR61)
Operating / Storage Condition	0°C ~ 50°C (32°F ~ 122°F) below 80%RH -10°C ~ 60°C (14°F ~ 140°F) below 70%RH
Dimensions	172mm × 118mm × 46mm
Weight	220g
Accessories	Instruction manual, Battery



INSTRUMENTOS DE MEDICIÓN INDUSTRIAL



LLÁMANOS

+52(81) 8115-1400 / +52 (81) 8173-4300

LADA Sin Costo:

01 800 087 43 75

E-mail:

ventas@twilight.mx

www.twilight.mx



/ [twilightsadecv](#)



/ [twilightsadecv](#)



/ [twilightsadecv](#)