

Medidor de temperatura/Humedad,temperatura de punto de rocío y bulbo húmedo, Sensor tipo Cable,Tenmars TM-183P







/ twilightsadecv



TM-183P

Temperature / Humidity Meter



- Dual display of temperature and humidity.
- Select between different temperature scales (°C / °F).
- Simultaneously hold both temperature and humidity readings.

- Simultaneously hold both Maximum and Minimum and Average readings

(MAX/MIN/AVG) with time marks.

- Relative subtraction value (REL) function.
- Alarm alert (SET) function.
- Auto-power off.
- DEW-POINT and WET-BULB temperature measurement.
- Stores up to 200 readings
- - Display: Dual LCD display. The maximum value on the primary display is 1999.
 - The maximum value on secondary display is 9999.
 - Low Battery Indicator: When the LCD displayssymbol, please replace the battery.
 - Sampling Rate: 1 sample per second.
 - Power Supply: One 9V battery, NEDA 1604, IEC 6F22 or JIS 006P.
 - Battery Life: 200 hours during consecutive use.
 - Dimensions: $200 \times 55 \times 38 \text{ mm} (L \times W \times H)(TM-183)$
 - $130 \times 56 \times 38 \text{ mm} (L \times W \times H)(TM 183P)$
 - Weight: 200g (excluding the battery)
 - Accessories: User manual, battery, carrying case , Temperature and humidity probe(TM-183P).
 - Operating Temperature and Humidity:0°C ~ +60°C,
 - Storage Temperature and Humidity: -10 to 60°C,
 - Temperature Measurement Range: -20.0°C ~ +60.0°C (-4.0°F Humidity)
 - Humidity Measurement Range: 1% ~ 99%RH.
 - Accuracy:Humidity : ±3% (20~80%RH,@25℃) ±5% (80%,@25℃) Temperature : ± 0.8℃, ±1.5°F



LLÁMANOS +52(81) 8115-1400 / +52 (81) 8173-4300

LADA Sin Costo: 01 800 087 43 75

E-mail: ventas@twilight.mx

www.twilight.mx





